

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number
WO 2004/059063 A2

(51) International Patent Classification⁷: **D04H 13/00**

(74) Agent: **KARAGHIOSOFF, Alessandro, Giorgio**; Studio Karaghiosoff e Frizzi S.a.s., Via Pecorile, 25, I-17015 Celle Ligure (IT).

(21) International Application Number:
PCT/EP2003/050990

(22) International Filing Date:
11 December 2003 (11.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(30) Priority Data:
SV2002A000063
30 December 2002 (30.12.2002) IT

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **EURO-PLASTICA S.R.L.** [IT/IT]; Via Bradisca, 65/67, I-33087 Pasiano di Pordenone (IT).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): **STEINBACH, Paolo** [IT/IT]; Salita Quarcino, 15, I-22100 Como (IT).

Published:

— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: THERMOPLASTIC FORMED PANEL, INTERMEDIATE PANEL FOR THE FABRICATION THEREOF, AND METHOD FOR FABRICATING SAID PANEL AND SAID INTERMEDIATE PANEL.



(57) Abstract: The invention relates to a thermoformable panel. According to the invention, the panel is composed of thermoplastic fibers forming a nonwoven fabric particularly having double crossed, randomized and thermally bonded webs, pressed under heating to cause a partial "melting" of the fibers, i.e. at least a partial loss of their fibrous phase and change into a viscous or viscoelastic phase, the relative distributions of the fraction of fibers that retain the fibrous phase and the fraction of plastic material that took the viscous or viscoelastic state depending on the depth thereof in the sheet thickness. The invention further relates to a formed, especially a highly embossed panel made of a thermoformable plastic material. The latter may be an intermediate semifinished product of a starting material. The invention also relates to a method for fabricating highly embossed panel. Particularly, the invention relates to a formed, especially a highly embossed panel and to the method for fabrication thereof, which highly embossed panel finds use in the automotive, naval, aerospace, railway and building industries, for the fabrication of interior or exterior coverings or structural members.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.